45" Built-in Electric Firebox

BF45DXP

Product Description

- Patented electric flame technology
- Built-in Purifire® air treatment system
- Pulsating embers and LED inner glow logs molded from wood logs for incredible realism
- Operates with flame only or with flame and heat
- Smooth edges allow for flush mounting to drywall/tile or for installation into a finished wall cavity
- Built-in manual switches main on/off, heater on/off.
- Unit may be wired with separate wall switches (not included) to control flame, Purifire and heater operation
- · Optional wall thermostat to control the heater.
- Dual 120 or 240/208 voltage compatible
- 120 Volts / 1,440 Watts / 4,915 BTU
- 208 Volts / 2,100 Watts / 7,170 BTU
- 240 Volts / 2,700 Watts / 9,220 BTU

Accessories

- TS521W Wall thermostat
- BFPLUGE 120 volt plug kit
- BFRC-KIT Remote control kit
- WRCPF-KIT Wall switch remote control








BF4TRIM45




BFDOOR45BLKSM





BFRC-KIT





Model #	Description	lbs/kg	UPC	Wty. †	Carton Dimensions (W x H x D)		Cube	
					Inches	cm	ft ³	m ³
BF45DXP	45" built-in electric firebox	110 / 50	781052 052390	2 yr.				
BFDOOR45BLKSM	Single pane, bi-fold look glass door kit	21 / 9.5	781052 041271	1 yr.	45.8 x 35.5 x 17.5	116.2 x 90.2 x 44.5	16.4	0.47
BF4TRIM45	4 pc. Black decorative raised profile trim	7 / 3.2	781052 052970	1 yr.	44.3 x 24.8 3.3	112.5 x 63 x 8.4	2.1	0.06
BF4TRIM45SS	4 pc. Stainless steel decorative raised profile trim	6 / 2.7	781052 052987	1 yr.	49 x 4.3 x 2.5	124.5 x 10.8 x 6.4	0.3	0.01

Patent protected: for a complete list of applicable patents visit: www.dimplex.com/patents. Specifications, finishes and dimensions are subject to change and should be taken as a quide only.

^{*} Based on average national residential electricity rates. Rates vary. † Limited warranty. © 2011 Dimplex North America Limited.