



Smart Heating Solutions

Commercial Unit Heater Program



Featured Inside:

PLATINUM^X

Includes It All.



*Introducing KB Platinum^X
Electronic Smart Unit Heater with IR Remote Control*

PLATINUM^X

LIMITED
5 Year
Warranty

Includes It All.



PlatinumX Controller

208/240/277/480 Volts 3KW-40KW 1 or 3 Phase

Features

- Energy-Saving PlatinumX Electronic Temperature Controller
- Built-In Provision For Using Any 24V Remote Thermostat (Optional)
- Remote Control Included with Wall Holder
- Summer Fan Only & Timer Modes
- Auto Memory Feature: Returns Unit To Last Settings After Power Outage
- Adjustable Louvers to Direct Air
- Built-In Fan Delay to Dissipate Heat
- High Mass Steel Fin Heat Exchanger
- Permanent Lubricated Unit Bearing Motor
- Universal Wall/Ceiling Bracket Included



Large Warehouse Coverage

10,239-136,520 BTU
520-3,500 CFM

Electronic 2-Stage Garage Heater

KB ECO2S Series



With U.S. & Global Materials



208/240 Volts 4KW-15KW 1 Phase

Features

- Smart ECO2S Energy-Saving Design
- 2-Stage Heating: Automatically Uses Lowest Wattage Needed
- Hand Held Remote Control & Wall Holder Included
- Timer & Summer Fan Only Modes
- Auto Memory Feature: Returns Unit To Last Settings After Power Outage
- Built-In Fan Delay To Dissipate Heat
- High Mass Steel Fin Heat Exchanger
- Permanent Lubricated Unit Bearing Motor
- Universal Wall/Ceiling Bracket Included

Upgrade To ECO2S+



Remote
Temperature
Sensor
(Included)

Added Features to ECO2S+

- ECO2S Remote Temperature Sensor
- Built-In Provision For Using Any 24V Remote Thermostat (Optional)
- Optional Power Supply For ECO2S Temp Sensor # ECO2S-5V-PWRSPPLY, Purchased Separately.



UP TO 1500 SQ FT

13,652-51,195 BTU

520-1050 CFM

Compact KBP Series



Pic-A-Watt
Steel Fin Element

LIMITED
5 Year
Warranty



With U.S. & Global Materials



120/208/240/277/480 Volts 950W-6KW 1 or 3 Phase

Features

- Pic-A-Watt® steel fin element
- Multiple wattage selection
- Long life cast iron motor
- Built-In thermostat
- Selector Switch: Fan/Heat/Off
- Fan Delay To Dissipate Heat
- Universal Wall/Ceiling Bracket Included



UP TO 700 SQ FT

**3,242-20,478 BTU
270 CFM**

Compact Heavy Duty SKB Series



LIMITED
3 Year
Warranty



With U.S. & Global Materials



208/240 Volts 5KW-10KW 1 Phase

Features

- Built-In thermostat to Control Comfort
- Adjustable Louvers to Direct Air
- Power On & Over-Temp Indicating Lights
- High Mass Steel Fin Heat Exchanger
- Permanent Lubricated Unit Bearing Motor
- Universal Wall/Ceiling Bracket Included



UP TO 1100 SQ FT

**17,000-34,100 BTU
520-800 CFM**

Heavy Duty KB Series



**LIMITED
3 Year
Warranty**

**MADE IN
USA**
With U.S. & Global Materials

**SMART
SLP
LIMIT**
PROTECTION

**c UL US
LISTED**

208/240/277/480 Volts 4KW-20KW 1 or 3 Phase

Features

- Adjustable Louvers to Direct Air
- Built-In Fan Delay to Dissipate Heat
- Built-In Thermostat
- High Mass Steel Fin Heat Exchanger
- Permanent Lubricated Unit Bearing Motor
- Universal Wall/Ceiling Bracket Included



**11,263-68,260 BTU
520-1,750 CFM**

High Air Velocity KFUH Series



**LIMITED
5 Year
Warranty**

**MADE IN
USA**
With U.S. & Global Materials

**c UL US
LISTED**

208/240/480 Volts 3.8KW-70KW 1 or 3 Phase

Features

- Heavy duty open coil element
- Direct drive air over type motor
- Dual inlet industrial blower
- Horizontal or vertical mount
- Adjustable louver
(sold separately)
- 22 Gauge Steel
- Ductable on Intake & Outlet
- 24 Volt Control
- Fan-Only Relay
- PSC Motor



**12,800-238,900 BTU
832-2,154 CFM**

Stainless Steel KBS Series



LIMITED
3 Year
Warranty

**MADE IN
USA**
With U.S. & Global Materials


SMART
SLP
LIMIT
PROTECTION

c **UL** US
LISTED

208/240/277/480 Volts 3KW-40KW 1 or 3 Phase

Features

- 304 Stainless Steel Construction
- For Areas Requiring Periodic Hose-Down
- Adjustable Louvers to Direct Air
- Permanent Lubricated Unit Bearing Motor
- High Mass Steel Fin Heat Exchanger
- N.E.M.A. 4 Enclosure
- Provision for remote thermostat*



High Air Velocity KFUH ECO2S Series



LIMITED
5 Year
Warranty

**MADE IN
USA**
With U.S. & Global Materials

c **UL** US
LISTED

208/240/480 Volts 3.8KW-70KW 1 or 3 Phase

Added Features to KFUH ECO2S

- Energy Efficient ECM Motor
- 2-Stage Comfort Heating
15% Savings
- 5 Speeds

ECO
ENERGY SAVING

eco2s








Smart Heating Solutions



Commercial Unit Heaters

									
Item Number	KBP	SKB	KB	KB ECO2S	KB ECO2S+	KB PlatinumX	KBS	KFUH	KFUH ECO2S
Category	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater	Unit Heater
Application	Up to 2 Car Garage	Up to 3 Car Garage	Large Facility Coverage	Up to 4 Car Garage	Up to 4 Car Garage	Large Facility Coverage	Up to 4 Car Garage	Large Facility Coverage	Large Facility Coverage
Max SqFt (8Ft Ceiling)	Up to 700 Sqft	Up to 1,000 Sqft	Up to 4,000 Sqft	Up to 1,500 Sqf	Up to 1,500 Sqf	Up to 4,000 Sqft	Up to 1,500 Sqft	Up to 3,500 Sqft	Up to 3,500 Sqft
Voltage	120/208/240/277/480	240	208/240/277/480	208/240	208/240	208/240/277/480	208/240/277/480	208/240/480	208/240/480
Wattages Available	950 - 6,000	5,000 - 10,000	4,000 - 20,000	4,000 - 15,000	4,000 - 15,000	3,000 - 40,000	3,000-40,000	3,800 - 70,000	3,800 - 70,000
Phasing Available	1PH or 1-3PH	1PH	1PH, 3PH or 1-3PH	1PH	1PH	1PH, 3PH or 1-3PH	1PH, 3PH or 1-3PH	1PH or 3PH	1PH or 3PH
Power Supply	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired	Hardwired
BTU Output	3,242 - 20,478	17,000 - 34,100	11,263 - 68,260	13,652 - 51,195	13,652 - 51,195	10,239 - 136,520	10,200 - 136,500	12,800 - 238,900	12,799 - 238,910
CFM	270	520 - 800	520 - 1,750	520 - 1,050	520 - 1,050	520 - 3,500	520 - 3,500	832 - 2,154	708 - 2,142
Temperature Rise	11°F - 67°F	40°F - 44°F	20°F - 45°F	30°F - 45°F	30°F - 45°F	20°F - 45°F	20°F - 45°F	15°F - 51°F	8°F - 69°F
Air Throw	12 ft	16 ft - 24 ft	15 ft - 37 ft	15 ft - 33 ft	15 ft - 33 ft	15 ft - 43 ft	15 ft - 43 ft	60 ft - 110 ft	60 ft - 110 ft
Energy-Saving 2-Stage Heating	NO	NO	NO	YES	YES	NO	NO	Option Available	YES
Built-In Thermostat	Bi-Metal	Bi-Metal	Bi-Metal	Electronic	Electronic w/Remote Temperature Sensor	Electronic	Bi-Metal	NO	NO
24V Remote Thermostat Control	NO	NO	NO	NO	Connections Provided for 24V Remote Stat	Connections Provided for 24V Remote Stat	Option Available	Connections Provided for 24V Remote Stat	Connections Provided for 24V Remote Stat
Adjustable Louvers	NO	YES	YES	YES	YES	YES	YES	Accessory Sold Separately	Accessory Sold Separately
Power Indicator Light	NO	YES	NO	YES	YES	YES	NO	NO	NO
ON/OFF Switch	YES	NO	NO	YES	YES	YES	NO	NO	NO
High/Low	NO	YES (except 5kW)	NO	YES	YES	NO	NO	NO	NO
Fan Only Switch	YES	NO	NO	YES	YES	YES	NO	YES	YES
Built-In Timer	NO	NO	NO	1-9 Hours	1-9 Hours	1-9 Hours	NO	NO	NO
Element Construction	Pic-A-Watt	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	Spiral Fin	NiChrome Open Coil	NiChrome Open Coil
High Limit Safety Control	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Self-Hold	Auto Reset	Auto Reset
Auto Fan Delay	YES	YES (except) 5kW	YES	YES	YES	YES	YES	NO	NO
Mounting Bracket	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Wall / Ceiling	Brackets for Threaded Rod	Brackets for Threaded Rod
Instruction Manual	YES	YES	YES	YES	YES	YES	YES	YES	YES
Mounting Diagram	YES	YES	YES	YES	YES	YES	YES	YES	YES
Warranty	5 Year	3 Year	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year	5 Year
Factory Tech Support	YES	YES	YES	YES	YES	YES	YES	YES	YES
Electronic Controls	NO	NO	NO	YES	YES	YES	YES	NO	NO
Remote Control	NO	NO	NO	YES	YES	YES	YES	NO	NO
Made In USA	YES	YES	YES	YES	YES	YES	YES	YES	YES

