



A BREATH OF FRESH AIR FOR YOUR GUESTS

When you need to bring in and dehumidify continuous outside make-up air into your guest's room through the PTAC, the **Amana®** brand DigiAIR® can assist. The guest room can be occupied, unoccupied or you can base it on any schedule you like, even 24/7/365.

The **Amana** brand DigiAIR module is a factory-installed make-up air system with configurable dehumidification. The DigiAIR system can provide continuous makeup air and will allow dehumidified outside make-up air to be introduced into the guest rooms. An optional 250 Watt supplemental heater, to warm the incoming air in colder climates, can be factory installed in every DigiAIR system.

DigiAIR system's adaptive dehumidification process activates dehumidification using a two tier temperature and outdoor relative humidity system. The DigiAir operational settings are fully configurable using the **Amana** brand PTAC mobile app or through the Eden Energy Management System.

- Combine with our full Eden™ EMS system to allow DigiAIR operation based on room occupancy. The full Eden EMS system also allows for quick and easy configuration of not only DigiAir settings, but all PTAC settings and unit health feedback.
- Configurable via the **Amana** brand PTAC mobile app or optional web interface
- Permanent washable filter
- 250 Watt supplemental heater (optional)
- **Amana** brand PTAC is AHRI certified

PMH R32 J Models							
Model	PMH073J **AXXX	PMH093J **AXXX	PMH123J **AXXX	PMH153J **AXXX	PMH074J **AXXX	PMH094J **AXXX	PMH124J **AXXX
Cooling							
Voltage	230/208	230/208	230/208	230/208	265	265	265
Capacity (BTU/h)	6,900/6,700	8,700/8,700	11,400/11,200	14,400/14,200	7,300	9,000	12,000
Amps	4.4/4.4	5.2/5.2	6.7/6.7	8.1/8.1	3.8	4.5	5.8
Watts	545/525	700/695	1,005/970	1,410/1,350	585	730	1,090
EER	12.6/12.7	12.4/12.5	11.3/11.5	10.2/10.5	12.4	12.3	11.0
Heating							
Capacity (BTU/h)	6,200/6,100	7,800/7,600	10,600/10,400	13,900/13,700	6,500	8,000	11,300
Amps	4.4	5.2	6.7	8.1/8.1	3.8	4.5	6.7
Watts	505/495	635/615	940/920	1,355/1,295	540	670	1035
COP	3.6/3.6	3.6/3.6	3.3/3.3	3.0/3.1	3.5	3.5	3.2
CFM (cooling)	339/339	312/312	291/293	354/354	339	312	311
CFM (heating)	378/378	345/345	320/323	370/370	378	345	327
Kit fresh air, CFM*	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35

PMC R32 J Models								
Model	PMC073J **AXXX	PMC093J **AXXX	PMC123J **AXXX	PMC153J **AXXX	PMC074J **AXXX	PMC094J **AXXX	PMC124J **AXXX	PMC154J **AXXX
Voltage	230/208	230/208	230/208	230/208	265	265	265	265
Capacity (BTU/h)	6,800/ 6,700	9,000/ 8,700	11,800/ 11,700	14,500/ 14,400	6,800	9,000	11,800	14,500
Amps	4.4/4.4	5.2/5.2	6.7/6.7	8.1/8.1	3.8	4.5	5.8	7.2
Watts	535/520	730/715	1,025/1,015	1,390/1,370	535	750	1,070	1,380
EER	12.7/12.8	12.3/12.1	11.5/11.5	10.4/10.5	12.7	12	11	10.5
CFM	342/342	318/318	316/316	412/412	342	318	316	412
Kit fresh air, CFM*	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35	25 - 35
Kit dehumidifier (oz./hr.)	5	5	5	5	5	5	5	5

*Actual vent CFM performance will vary due to application and installation conditions. 95 CFM with Power Vent Fan option (Feature Code "v").
Actual CFM will be conditional on building pressure

PTAC limited warranty:

- First-year warranty: parts & labor
- Second through fifth year: parts & labor on certain sealed system components (PTAC's primary sealed system)
- Second through fifth year: on certain functional parts only

* Complete warranty details available from your local dealer or at www.amana-ptac.com



Amana PTACs are certified for performance by the American Heating and Refrigeration Institute and listed by ETL for UL 484 compliance.



CALL YOUR **AMANA BRAND** PTAC SALES REPRESENTATIVE AT 800-647-2982 FOR COMPLETE DETAILS.

Before purchasing this appliance, read important information available from your retailer about its estimated annual energy consumption, yearly operating cost or energy efficiency rating.

DigiAIR

Your PTAC Make-up
Air Solution