

# GE® Tankless Electric Water Heater

## Model# GE24DNHPDG



**GE APPLIANCES**  
a Haier company

*CustomerNet*



### FEATURES

Uniform Energy Factor (UEF)	>0.91
Flowrate (GPM) @ 47 F inlet	3.09
Flowrate (GPM) @ 37 F inlet	2.7
Flowrate (GPM) @ 77 F inlet	6
Flowrate (GPM) @ 62 F inlet	3.9
Min. operating pressure (psi)	25
Controls	Adjust degree Fahrenheit/Celsius Adjustable Temperature Digital Electronic Control
Max. operating pressure (psi)	150
Max. operating pressure (psi)	150
Fuel Type	Electric
Flowrate (GPM) @ 57 F inlet	3.59
Configuration	Space Saver
Installation Location	Indoor
Flowrate (GPM) @ 72 F inlet	5.3
Temperature adjustment amount (degree)	1
Activation Flowrate (GPM)	0.5
Temperature Setting Factory Default	105° F
Product Type	Electric Tankless
Flowrate (GPM) @ 52 F inlet	3.4
Integrated Safety Devices	Flow sensor¶High limit thermostat (on each heating element)¶Inlet Temperature Sensor¶Material Rated for Ignition Containment¶Outlet Temperature Sensor
Maximum Outlet Temperature (F)	140
Water	Bottom

- Unlimited Hot Water on Demand - Tankless electric water heater provides instant, continuous water flow
- Whole Home Solution - Easily provides enough hot water for a house or apartment
- Performance Up to 5.3 Gallons Per Minute (GPM) - Enough to run 2 showers and 4 faucets simultaneously in warm climates (\*Results are based on 72F inlet water temperature and 105F outlet water temperature)
- Intuitive Design - Adjust temperature and settings with easy-use touch screen
- Energy Efficient - Conserves energy and water by only using energy when hot water is in use, saving you money
- Space Saver - Compact design takes up significantly less space than a tank style water heater
- Scale Reduction Technology - Extends the life of the unit by shielding heating element from water and scale buildup
- Self Modulating Technology - Utilizes inlet and outlet temperature sensors to optimize energy usage and keep water temperature consistent
- Easy Installation - Uses standard 1/2-in NPT water connections and does not require venting for simple, wall-mounted water heater installation

- Digital Temperature Control - Easily set temperatures in 1° increments ranging from 86°F to 140°F
- Fahrenheit or Celsius - Switch temperature units with a simple tap on an easy-read digital display
- Warranty Length - 5-year Limited Replacement Warranty

Connection Location	
Point of Use	Whole Home
Cold/hot water connections (inches)	3/4" Cold Water Inlet; 3/4" Hot Water Outlet
Flowrate (GPM) @ 67 F inlet	4.59
Temperature Setting	86-140° F Range
Flowrate (GPM) @ 42 F inlet	2.9

Have more questions? Please contact 1-800-626-2000

# GE® Tankless Electric Water Heater

## Model# GE24DNHPDG



**GE APPLIANCES**  
a Haier company

*CustomerNet*

### APPROXIMATE DIMENSIONS(HxDxW)

- 15.20 H x 10.20 W x 3.70 D

### APPEARANCE

- Installation - Wall Mounted
- Color Appearance - Diamond Gray

### WEIGHTS & DIMENSIONS

- Approximate Shipping Weight (lb) - 15 1/5lb
- Overall Width (in) - 10 1/5in
- Overall Height (in) - 15 1/5in
- Product Height (to top of unit) (in) - 15 1/5in
- Net Weight (lb) - 14 9/10lb
- Product Diameter (in) - 10 1/5in
- Overall Depth (in) - 3 7/10in

### POWER / RATINGS

- Power Rating-kW - 24
- Amps - 100.0
- Voltage (MAX) - 240V
- Electrical Circuit Required - 40 Amp (x3)

### WARRANTY

- Parts Warranty - 5-year Limited Replacement Warranty

### CERTIFICATIONS

- Claims & Certifications - ADA Compliant

*Have more questions? Please contact 1-800-626-2000*