

# GE® 36 Gallon Top Port Lowboy Electric Water Heater Model# GE40L08BAM



- Lowboy Make the most of tight spaces with a water heater that fits where height is a concern
- Household Size Provide hot water for the whole family of 2 to 4 persons
- Quick Recovery Two 5500W heating elements quickly increase water temperature for hot water when you need it
- Inlet Tube Replenishes water from the bottom of the tank to maximize hot water delivery
- Easy Set Up Replace your old water heater quickly and easily using standard water and electrical connections
- Anode Rod Durable design offers long-lasting protection against corrosion
- Drain Valve Rust-proof construction can be counted on to provide long-lasting service
- Adjustable Thermostat Change temperature to your desired setting

## **FEATURES**

Control Type	Thermostat
Temp & Pressure Relief Valve	Yes
Rated Capacity	36gal
Height Description	Low Boy with Top Port
Fuel Type	Electric
Configuration	Lowboy
Installation Location	Indoor
Operating Modes	Standard Electric
Rated Storage Capacity	36
Drain Valve Type	Plastic
GPH Recovery @ 90 Degrees F	25.1
Mobile Home Compatible	No
Temperature Setting Factory Default	120° F
Product Type	Electric Thermostat
Family Size	2-4 People
Water Connection Location	Тор
Foam Insulation	Yes
Point of Use	No
Temperature Setting	90-150° F Range
Insulation Thickness	2.75in

Have more questions? Please contact 1-800-626-2000



# GE® 36 Gallon Top Port Lowboy Electric Water Heater Model# GE40L08BAM

## APPROXIMATE DIMENSIONS(HxDxW)

• 32 3/4 H x 27 W

## **CAPACITY**

• Unit Capacity - 40 Gallons

#### **APPEARANCE**

· Color Appearance - Gray

### **WEIGHTS & DIMENSIONS**

- Product Height (to top of water inlet/outlet connections) (in) - 34 1/4in
- Approximate Shipping Weight (lb) 145lb
- Overall Width (in) 27in
- Overall Height (in) 32 3/4in
- Product Height (to top of unit) (in) 32 3/4in
- Net Weight (lb) 135lb
- Product Diameter (in) 27in
- Connection Sizes Water Inlet (MNPT) (null) 3/4"
- Connection Sizes Hot Water Outlet (MNPT) (null) 3
  /4"

## **POWER / RATINGS**

- Integrated Energy Factor 0.92
- Heating Electric Heater Watts 5500/5500
- Electrical Connection Direct-Wire
- Operating Water Pressure 20-125 PSI
- Volts/Hertz 240V; 60Hz
- First Hour Rate (FHR) 61 Gallons
- Voltage (MAX) 240V
- Electrical Circuit Required 208V/240V 60 Hz Dedicated 30 Amp Min.

## **WARRANTY**

- Warranty Notes See written warranty for full details
- Parts Warranty 8-year limited
- Labor Warranty 1-year limited

### **CERTIFICATIONS**

• Claims & Certifications - California Prop 65

Have more questions? Please contact 1-800-626-2000